

215								12		12	:lstoT				_						
215		o	¥710°1\$	8/12/2018	Stock	ZZ†090S	2	21	4/12/2018	St				Tool Steet Round Bar 0.125 dia.	l I	-10-TM SS1 0R			€	VU MCM001-	8596E0O
toT	Past	gnigA sysG	Price/Unit	Receive Date	sutet2	Container oM	Accounting of dot	Received	Due	Order	Equipment ID	Project	For Part No	Description	pa	Purchas Item	emnəT	Rel	Line	Supplier	on Od

https://www.plexonline.com/fb1be0eb-35c4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp?Opener_Session_Key={FB1BE0EB-35C4-4772-98a3-5600bb723c01/Plexus_Control/Report_Viewer_S.asp.

Plex 4/12/2018 T1:20 AM Dart Dubois, Pascal

PURCHASE ORDER 8239558

Plex 4/10/18 11:08 AM dart.lavoie.chanta

Dart Aerospace Ltd. 1270 Aberdeen St Hawkesbury, ON Ganada



Tel (613) 632-5200

011	50									
80.016\$	Grand Total:				S	eto Note	40			
87.6\$	#/87E0.0\$	1001	1 0	11 00 f	4/12/18	рәші	niq gninqS	100/pk	EPIAETESE	9
	7-1-1-1-1-1	y			- provide to beautiful	V-1-1-1-1-1		, rone	6 PCS OF 20	etoN metl eni.
81.03\$	#/ÞZ810.9\$	n or	¥О	fi Of	4/12/18	pəmii	Extension Spring, SS, 20" Long x 0.25" OD x 0.02" Dia.	1/bk	9665K57	g
						ger in ner man, and		1" X 24"	4 PCS OF 24	etoN mett eni.
42.881\$	12/297.118	18 91	165°0 st	1s 9t	81/21/18	рәшід	Adhesive Backed Foam Color Grey	X 3/4"	8865K62	Þ
\$12.14	\$1.0116666/R		¥0 ~1	121	81/21/4	bərmi	Tool Steel Round Bar 0.125 dia.	e il long 8893K148	-10-TM 70.125	8
\$33.04	\$8.26/Ea	63 A	s3 0	B∃ Þ	81/21/4	Pirmed	Wrench, 7/16 Hex Drill, Power #2	99A5333	482X	2
	· · · · · · · · · · · · · · · · · · ·						The second of the second second second	9199	JOB NO. 17	ine Item Note
\$12.70	63\72.1\$	10 Ea	63 0	10 Ea	4/12/18	Pirmed	Breather Vent AS PER DWG D5540 REV. A		9833KZ1	ı
Extended Price	Unit (DSU) esinq	Balance	Received Quantity	Order Quantity	Due Date	Status	Description	Supplier Part No	hsq	eni. metl
						Items				
		enordlistr	/12/18 avoie, Char lavoie@dar iround % 10 Net 3	rder ntact: L c : 2 : S	e Date: chase O vision: vision Da vision Os	Pure Rev Rev Shin	A	5 5500 600 Street	O. Box 7690 hicago, IL 606 hone: 330 995 9 270 Aberdeen awkesbury N A 1K7 Canad	Ship To:
			90039558		No: Date:			Supply Co,	CMaster-Carr	N

68-6

SAG

MACERIAL RECEIPT INSPECTION FORM

	810	5 5	1 99Ae8-8			
SIGNED OLE BA:	-		SAG	NSPECTED BY:	I	
ENGINEERING SIGNOFF (if required			370	8 INSPECTION	30 18	
ated in the Quality Office						
osiMO villenO odt ni hote	JOI STOTS	-	וומעדען עדע	ONESS / DOROME	7.1.7.	
		1		OF TEST SAMPLE		
		1	=	OF MATERIAL		
C HRB DURA DURD WEBSTER	HH	1		IVIODITAN DO S	POVI	
D RESULTS BELOW		Н				
SIAL AND PREFORM A HARDNESS CHECK.			WPLE PIECE	AS 100		
			10110 11011	VO 1110		
	TAI	-	1210	IZVI NOIGOVI VZ		
	N	٨		DOES THIS REQUI		
	N	1		ENGINEERING SIG		
	0	^		JAIRATAM SIHT 830	DΩ	
	N	(1)		RRECT M# ON THE		
	. N	家		RECT MATERIAL ID		
84178688#179-855680#Pd #1698	AN	33		ORRECT REF # TO I		
* * * * * * * * * * * * * * * * * * * *	N	1		PHOTO REQUI		
	N	W	CNESS	CORRECT THICK		
189H 1973	7 N	(1)	SM-DRAWING	RECT MATERIAL PER	СОВ	
	N		RECTION	ORRECT GRAIN DI	0	
	(N)	4	N	CORROSIO		
	N	W		CORRECT FIN		
	(N)	٨	AGE	SURFACE DAM		
	(N	//				
COMMENTS	GCK		NC	DESCRIPTION		
	A:	NC				

Attach this inspection sheet with the corresponding material cert and remit to be scanned and received in

: BTAG

SPECIFICATION CONTROL DRAWING

PURCHASE MATERIAL: AISI O1 TOOL STEEL ROUND BAR

SPECIFICATION:

DIN 1.2510 or B.S. BO 1 or SAE J437 or SAE J438 or UNS T31501 or ASTM A681

PART NUMBER:

MT-01-R [D.DDD] WHERE "D.DDD" = DIAMETER IN INCHES

EG. 5/8" ROUND BAR = MT-O1-R0.625

w

DESIGNARY: VAN 8/9/2017 AX \$\frac{1}{2} \text{ACT COSS 8.18} \\
DOSSON REV: VAN 8/9/2017 AX \$\frac{1}{2} \text{ACT COSS 8.18} \\
DOSSON REV: VAN 8/9/2017 AX \$\frac{1}{2} \text{ACT COSS 8.18} \\
DOSSON REV: VAN 8/9/2017 AX \$\frac{1}{2} \text{ACT COSS 8.18} \\
DOSSON REV: VAN 8/9/2017 AX \$\frac{1}{2} \text{ACT COSS 9/9/2017} \\
DOSSON REV: DED 9/9/1/2/2017 AX \$\frac{1}{2} \text{ACT COSS 9/9/2017} \\
DOSSON REV: DED 9/9/1/2/2017 AX \$\frac{1}{2} \text{ACT COSS 9/9/2017} \\
DOSSON REV: DES 9/9/2/2017 AX \$\frac{1}{2} \text{ACT COSS 9/9/2017} \\
DOSS 9/9/2/2017 AX \$\frac{1}{2} \text{ACT COSS 9/9/2017} \\
D AISI O1 TOOL STEEL ROUND BAR DART OF

0

0

A REV.

DESCRIPTION NEW ISSUE

17.08.09 DATE

νw

APPROVED MW

McMASTER-CARR.

Tool Steel

For information about steel, see page 3794.

Tight-Tolerance Multipurpose O1 Tool Steel Rods



- · Yield Strength 50,000 psi
- · Hardness, Rockwell B90 (Medium)
- · Heat Treatable: Yes
- Max Hardness after Heat
 Treatment
 To a see: Rockwell C65
 Metric sizes: Rockwell C65
 Metric sizes: Rockwell C65
 Specifications Max 1681

.900000 04 ..900000- ...951.0

These precision-ground rods have a tight diameter tolerance. Commonly used for dies, punches, and gauges. Ot tool steel is an oil-hardening material that resists wear and abrasion.

17.8

5.5 3.5 3.1	67 66 1 \$	-Б-7	8893K115	Precision Ground	Softened (Annealed)	Dia. Tolerance -0 0005" to 0 0005"	Dia. 0.0625" 0.063"
1.5		40.000.00					
	17.1		711 XE688	MINISTER GOISINGTH			
		Personal.		Precision Ground	(belsennA) beneffod	"2000.0 of "2000.0-	
3.3	1.84		8893K118	Precision Ground	Softened (Annealed)	"8000.0 of "8000.0-	990 0
3.6	2.03		8893K119	Precision Ground	(balsannA) banaffo2	"2000 0 ot "2000 0-	"690°0
17	2.29	invision	8893K121	Precision Ground	Softened (Annealed)	"8000 0 of "8000 0-	"STO.0
4.4	74.5	**********	8893K122	Precision Ground	Softened (Annealed)	"2000.0 of "2000.0-	.9400
8.4	2.66	***************************************	8893K123	Precision Ground	(belseanA) benefic2	"2000 0 of "2000 0-	"5870.0
1.3	2.84		8893K125	Precision Ground	Softened (Annealed)	"8000 0 of "8000 0-	"2870.0
6.4	2.74	-	8893K126	Precision Ground	Softened (Annealed)	"2000,0 of "2000,0-	.6200
1.8	2.85		8893K127	Precision Ground	Softened (Annealed)	"3000 0 of "3000 0	"180,0
9.8	3.10	-1246000	8893K126	Precision Ground	Softened (Annealed)	"3000 0 01 "3000 0	"880,0
2.9	3.43	-	8893K129	Precision Ground	(belsennA) benefical	"2000.0 of "2000.0-	"880.0
7.9	3.71		8893K131	Precision Ground	Soffened (Annealed)	"2000 0 of "2000 0"	"SE00.0
0.4	2.25	********	8893K133	Precision Ground	(balsannA) banaflo2	"2000 0 of "2000 0-	860.0
3.6	2.01	-	8893K134	Precision Ground	Softened (Annealed)	"2000.0 of "2000.0-	
3.7	2.05		8893K135	Precision Ground	Softened (Annealed)	"2000.0 of "2000.0-	
0.4	2.24	-	8893K136	Precision Ground	Softened (Annealed)	"3000 0 ot "3000 0	"860.0
4.2	2.31	commen	8893K137	Precision Ground	Softened (Annealed)	"2000,0 of "2000,0-	"101.0
4.3	2.40		8893K138	Precision Ground	Softened (Annealed)	"2000.0 of "2000.0-	0.103"
9.4	2.49	Problems	8893K139	Precision Ground	Softened (Annealed)	"3000 0 of "3000 0	.9010
8.4	2.66		8893K141	Precision Ground	Softened (Annealed)	"2000 o ot "2000 o	"801.0
1.3	2.84	Witness.	8893K143	Precision Ground	Softened (Annealed)	"3000 0 ot "3000 0-	
6.4	2.71	***************************************	8893K144	Precision Ground	Softened (Annealed)	.9000 0 ot9000 0	"110
1.3	2.83		8893K145	Precision Ground	(beisennA) benehod	"3000 G of "3000 G	0.112"
5.3	2.93	- Constant	8893K146	Precision Ground	Softened (Annealed)	"2000.0 of "2000.0-	211.0
6.8	3.28	-4	\$893K147	Precision Ground	Softened (Annealed)	"8000 0 of "8000 0-	210
0.0	3.34	-	8893K148	Precision Ground	Softened (Annealed)	,5000 0 oi ,5000 &	"841.0
		k)	u d is word		-
		1	1	f O eacognig	Product Detail Tight-Tolerance Multi		2
					Tool Steel Rod, 0, 125		
				leats loot gnits	Guidelines for Heat Tre		
					Length, ft.		
					9		
					Each		
					A30A0 OT OQA		
66.4	17.5		8893K121 8893K149	Precision Ground Precision Ground	Softened (Annealed) Softened (Annealed)	-0.0005" to 0.0005" -0.0005" to 0.0005"	0.127"
96'9	3.28		8893K152	Precision Ground	Softened (Annealed)	"2000.0 of "2000.0-	0.138
31.9	3.40	-	8893K153	Precision Ground	Softened (Annealed)	"2000 0 ot "2000 0-	
6.23	3.43	10000000	8893K154	Precision Ground	Softened (Annealed) Softened (Annealed)	"6000,0 of "8000,0-	0.146"

Softened (Annealed) Precision Ground 8893K156